

24" Data Centre Racking

Key Features

- Flexible and modular racking system
- Sturdy aluminium uprights on a uniquely rigid set of metal infills
- Internally reduced to 19"
- Perforated front and rear doors.
- Easy to join and buying.
- Raised top for ventilation
- Adjustable feet (levelling screws)
- Hinged and removable metal side panels and rear door
- Split front and rear doors
- Additional 100mm on either side for Cable Management
- Cable entry made possible from top or bottom
- Full range of accessories available.
- Fitted with high tensile security "combination lock"
- Standard 3 point locking system applied
- Available in 43u and 47u Heights
- Adjustable depth reducers
- Adjustable punched profiles
- All metal components are epoxy powder coated
- Complies to DIN41494 specifications (sections 1-4) as well as ANSI/EIA-310-D-1992
- AdleRac® is an SABS ISO 9001:2008 certified manufacturer

Platinum Range

- This rack features a range of aesthetic enhancements and features including ventilated front and rear panels
- Fully configurable to customer requirements
- The system is designed with the unique requirements of every customer in mind and can easily be configured to suite these unique requirements. This is accomplished by us providing a large range of standard components and accessories which can be fitted to the rack with ease.



Technical Specifications

Rack Height 43U	800 x 1,2 m x 24"
Net Weight	189 KG
Maximum Height	2120 mm
Maximum Width	800 mm
Maximum Depth	1200 mm
Shipping Weight	210.9 KG
Shipping Height	2150 mm
Shipping Width	830 mm
Shipping Depth	1230 mm
Weight Capacity (static load)	1363.64 KG
Weight Capacity (dynamic load)	1022.73 KG
Minimum Mounting Depth	262.00 mm
Maximum Mounting Depth	1000 mm
Color	Black or Grey

Technical Specifications

Rack Height 47U	800 x 1,2 m x 24"
Net Weight	190 KG
Maximum Height	2300 mm
Maximum Width	800 mm
Maximum Depth	1200 mm
Shipping Weight	220.9 KG
Shipping Height	2330 mm
Shipping Width	830 mm
Shipping Depth	1230 mm
Weight Capacity (static load)	1363.64 KG
Weight Capacity (dynamic load)	1022.73 KG
Minimum Mounting Depth	262.00 mm
Maximum Mounting Depth	1000 mm
Color	Black or Grey